

# Constellation™



## One unified power/data platform—so many applications

Constellation is a streamlined, modular and adaptable power/data delivery platform designed specifically for today's hyperconnected enterprise networks. Featuring modular components deployed in a simplified, repeatable architecture, Constellation easily adapts to meet the power and data needs of virtually any connected environment—from airports, educational campuses and data centers to office buildings, stadiums, warehouses and more. The result is a simplified, scalable network that can dramatically reduce the time, cost and complexity of supporting connected devices, in-building and across campus.

## REFERENCE ARCHITECTURES

Education .....	2
Multi-tenant data center .....	3
One-level building .....	4
Stadium/large venue .....	5
Warehouse/manufacturing .....	6
Airports/transportation hubs.....	7
Hospitality .....	8
Healthcare .....	9















COMMSCOPE®


## Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

### LEGEND

-  High-powered fiber cable
-  Singlemode patch cord
-  IP devices
-  Powered fiber for ERA® UAP-2
-  IP BAS controller with power
-  BAS device wiring
-  Propel™ fiber shelf
-  Aggregation/core fiber switch
-  ERA® UAP
-  Constellation convergence point
-  PoE switch (inside Constellation Point)
-  Power transmitter
-  Power transition panel
-  Building automation controller



# Multi-tenant data center

COMMSCOPE®


## Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

### LEGEND

- High-powered fiber cable
- Singlemode patch cord
- IP devices
- Powered fiber for ERA® UAP-2
- IP BAS controller with power
- BAS device wiring
- Propel™ fiber shelf
- Aggregation/core fiber switch
- ERA® UAP
- Constellation convergence point
- PoE switch (inside Constellation Point)
- Power transmitter
- Power transition panel
- Building automation controller



# One-level building

COMMSCOPE®


## Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

### LEGEND

- High-powered fiber cable
- Singlemode patch cord
- IP devices
- Powered fiber for ERA® UAP-2
- IP BAS controller with power
- BAS device wiring
- Propel™ fiber shelf
- Aggregation/core fiber switch
- ERA® UAP
- Constellation convergence point
- PoE switch (inside Constellation Point)
- Power transmitter
- Power transition panel
- Building automation controller

















COMMSCOPE®


## Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

### LEGEND

-  High-powered fiber cable
-  Singlemode patch cord
-  IP devices
-  Powered fiber for ERA® UAP-2
-  IP BAS controller with power
-  BAS device wiring
-  Propel™ fiber shelf
-  Aggregation/core fiber switch
-  ERA® UAP
-  Constellation convergence point
-  PoE switch (inside Constellation Point)
-  Power transmitter
-  Power transition panel
-  Building automation controller




## Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

COMMSCOPE®



SIDE VIEW

REAR VIEW

LEGEND

- |                          |                              |                              |                               |                                 |   |                                |
|--------------------------|------------------------------|------------------------------|-------------------------------|---------------------------------|---|--------------------------------|
| High-powered fiber cable | Powered fiber for ERA® UAP-2 | BAS device wiring            | Aggregation/core fiber switch | Constellation convergence point | Power transmitter                       | Building automation controller |
| Singlemode patch cord    | IP devices                   | IP BAS controller with power | Propel™ fiber shelf           | ERA® UAP                        | PoE switch (inside Constellation Point) | Power transition panel         |


# Airports/transportation hubs

## Constellation™ reference architectures















Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

COMMSCOPE®



### LEGEND

 High-powered fiber cable	 Powered fiber for ERA® UAP-2	 BAS device wiring	 Aggregation/core fiber switch	 Constellation convergence point	 Power transmitter	 Building automation controller
 Singlemode patch cord	 IP devices	 IP BAS controller with power	 Propel™ fiber shelf	 ERA® UAP	 PoE switch (inside Constellation Point)	 Power transition panel















## COMMSCOPE®



### Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

#### LEGEND

-  High-powered fiber cable
-  Singlemode patch cord
-  IP devices
-  Powered fiber for ERA® UAP-2
-  IP BAS controller with power
-  BAS device wiring
-  Propel™ fiber shelf
-  Aggregation/core fiber switch
-  ERA® UAP
-  Constellation convergence point
-  PoE switch (inside Constellation Point)
-  Power transmitter
-  Power transition panel
-  Building automation controller



















## COMMSCOPE®


### Constellation™ reference architectures

Note: Placement and quantity of Constellation Points are for demonstration of general architecture. Please see design guidelines to determine quantity of Constellation Points and placement.

Maximum distance from main equipment room is 500 meters with 1,000-watt power delivery.

#### LEGEND

-  High-powered fiber cable
-  Singlemode patch cord
-  IP devices
-  Powered fiber for ERA® UAP-2
-  IP BAS controller with power
-  BAS device wiring
-  Propel™ fiber shelf
-  Aggregation/core fiber switch
-  ERA® UAP
-  Constellation convergence point
-  PoE switch (inside Constellation Point)
-  Power transmitter
-  Power transition panel
-  Building automation controller



CommScope pushes the boundaries of communications technology with game-changing ideas and ground-breaking discoveries that spark profound human achievement.

We collaborate with our customers and partners to design, create and build the world's most advanced networks. It is our passion and commitment to identify the next opportunity and realize a better tomorrow. Discover more at [commscope.com](https://commscope.com).

**COMMSCOPE**<sup>®</sup>

---

[commscope.com](https://commscope.com)

Visit our website or contact your local CommScope representative for more information.

© 2023 CommScope, Inc. All rights reserved. CommScope and the CommScope logo are registered trademarks of CommScope and/or its affiliates in the U.S. and other countries. For additional trademark information see <https://www.commscope.com/trademarks>. All product names, trademarks and registered trademarks are property of their respective owners.

CO-117940-EN (08/23)